

Feuillure 53 x 16 Porte à chants droits




	Α	В
	73	52
	78	62
	88	74
	98	84
	108	92
	116	100
	128	112
Dimension standard	138	122
(Ax55)	148	132
(4,33)	158	142
	168	152
	178	162
	188	172
	198	182
	208	192

Feuillure 53 x 16 El 60 Porte à chants droits



		_
	Α	В
	73	52
	78	62
	88	74
	98	84
Dimension	108	92
	116	100
	128	112
standard	138	122
(Ax55)	148	132
	158	142
-	168	152
	178	162
	188	172
	198	182
	208	192


Feuillure 43 x 16 Porte à chants droits



	Α	В
	67	51
	73	52
	78	62
	88	74
	98	84
	108	92
Dimension standard	116	100
	128	112
(A x 55)	138	122
(AX33)	148	132
- - -	158	142
	168	152
	178	162
	188	172
	198	182
	208	192


Profil spécifique pour quincaillerie encastrée dans la traverse d'huisserie (verrouillage pour contrôle d'accès,ferme porte encastré)

Feuillure ISO 56 x 16 Porte à chants droits




	Α	В
	73	52
	78	62
	88	74
-	98	84
	108	92
	116	100
	128	112
Dimension	138	122
standard (A x 55)	148	132
	158	142
	168	152
	178	162
	188	172
	198	182
	208	192

Feuillure ISO 56 x 16 El 60 Porte à chants droits



	Α	В
	73	52
	78	62
	88	74
	98	84
	108	92
	116	100
Dimension	128	112
standard	138	122
(Ax55)	148	132
	158	142
	168	152
	178	162
	188	172
	198	182
	208	192

Feuillure ISO 46 x 16 Porte à chants droits Traverse Elargie



	Α	В
	67	51
	73	52
	78	62
	88	74
	98	84
	108	92
	116	100
Dimension standard	128	112
(A x 55)	138	122
(4,33)	148	132
	158	142
	168	152
	178	162
t	188	172
	198	182
	208	192

*: Entaillage 48x2 pour rail placo sur sections A = 88 et 116

